Safety Data Sheet (SDS)

1. Chemical Product and Company Identification

Product name Information on company	: Electrolyte for Nickel Cadmium battery for stationary (Potassium Hydroxide)
Company name	: THE FURUKAWA BATTERY CO., LTD
Address	: No.2-4-1 HOSHIKAWA, HODOGAYA-KU, YOKOHAMA, KANAGAWA, JAPAN
Department in charge	: Environmental promotion
Phone number	: 81-45-336-5055
Fax number	: 81-45-333-2534
Recommended use of the	: This product is the electrolyte of Nickel Cadmium battery.
chemical and restrictions on use	Please do not use for except to be filled in Nickel Cadmium battery.

2. Hazards Identification

GHS classification

Health hazards	
Acute toxicity (Oral)	: Category 4
Skin corrosion/ irritation	: Category 1B
Serious eye damage/ eye irritation	: Category 1
Specific target organ toxicity (Single exposure)	: Category 1 (respiratory organs)
Specific target organ toxicity (Repeated exposure)	: Category 1 (respiratory organs)
Aspiration hazard	: Category 1

*Regard to physical and chemical hazards, health hazards, environmental hazards, the classification not mentioned above is 'Not applicable', 'Classification not possible' or `Not classified' currently.

GHS label elements: Pictogram

.	- · · · ·
Signal words	: Danger
Hazard statements	: Toxic if swallowed.
	Causes severe skin burns and eye damage. Causes damage to organs (respiratory organ)
	Causes damage to organs through prolonged or repeated exposure (respiratory
	organ system).
	May be fatal if swallowed and enters airways
Precautionary statements	, ,
Prevention	: Do not breathe gas/mist/ vapours /spray.
	Wash hands thoroughly after handling.
	Do not eat, drink or smoke when using this product.
_	Wear protective gloves/protective clothing/eye protection/face protection.
Response	: Wash contaminated clothing before reuse.
	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Call a doctor.
	IF exposed or concerned: Get medical advice/attention if you feel unwell.
	IF SWALLOWED: Rinse mouth. Do not induce vomiting.
	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	If in eyes: Rinse cautiously with water for at least 15minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	If swallowed, if on skin (or hair), if inhaled, if in eyes, immediately call a doctor.
Storage	: Store locked up.
	1/6
	THE FURUKAWA BATTERY CO.,LTD Electrolyte for Nickel Cadmium battery for stationary (Potassium Hydroxide)

Disposal

Date of revision: 2023/9/20
 Entrust disposal of contents/container to the professional disposal contractor who has received the permission of the prefectural governor.
 No information.

Other risks/hazards

3. Composition/Information on Ingredients

Material		Annovinate 0/	
Components	Chemical Formula	Approximate % by Wt. or Vol.	CAS#
Potassium Hydroxide	КОН	21-25	1310-58-3
Water	H ₂ O	75-79	7732-18-5

Specific gravity:1.23

. First-aid Measures	
If inhaled	: Remove person to fresh air, keep comfortable for breathing.
	Get medical advice/attention.
lf on skin	: Take off or remove immediately all contaminated clothing. Rinse skin with water/ shower.
	If skin irritation or skin burns occurs, get medical advice/attention.
If in eyes	: Open the eyelids with your fingers, and wash with running water for at lea 15 minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	Get medical advice/attention.
If swallowed	: Immediately call a doctor.
	Rinse mouth.
	Do not induce vomiting.
	Get medical advice/attention.
Most important symptoms/effects, acute and delayed	:Burning sensation, sore throat, cough, breathlessness, shortness of breath redness, pain, blurred vision, blisters, severe skin burns, severe burns,
acute and delayed	abdominal pain, headache, nausea, shock or collapse, vomiting.
Protection for first-aiders	: Rescuers wear suitable protective equipment such as rubber gloves and
	tight-fitting safety goggles.
. Fire Fighting Measures	
Suitable extinguishing media	: Electrolyte itself does not have flammability and also not combustion supporting property. In Nickel Cadmium battery and electrolyte handling place and the like, extinguish fire using dry chemical or water when fire occurs.
Specific fire fighting method	: Move the container from the fire area if it is not dangerous.
	After extinguishing the fire, continue to cool the container thoroughly with plenty of water.
	Immediate move the movable container to safe place when fire occurs in surrounding.
Protection for fire-fighters	: Extinguish fire from upwind.
-	Wear appropriate respiratory protection or protective clothes for chemical when firefighting.

6. Accidental Release Measures	
Personal precautions, protective equipment and emergency measures	: Wear suitable protective equipment (gloves, protective glasses, protective clothing and the like), when processing the leakage. Do not touch or walk through the leakage.
	Do not breathe gas, mist, vapour and spray.
Precautions for the environment	: Be careful to not discharge the product into the rivers, sewer, and soil.
Method for containment and clean-	: Collect it in an empty airtight container.
ир	Absorb by sprinkling misty water when the gas is generated.
Prevention of secondary hazards	: Immediately remove all ignition sources in the vicinity.
,	Prepare fire extinguishing equipment just in case it is ignited.

7. Handling and Storage

Handling	
Technical measures	: Take measure described in '8: Exposure Controls and Personal Protective Equipment', and wear appropriate protective equipment.
Cautions for Safety Handling	: Wash hands, face and the like thoroughly and gargle after handling. Do not eat, drink or smoke when using this product. Do not breathe gas/ mist/ vapours /spray. Avoid contact with eyes and skin. Wear protective gloves/protective clothing/eye protection/face protection.
Storage	······································
Storage condition	 Provide a ventilation and lighting required for storing and handling hazardous materials in the storage location. Store locked up. Keep container tightly closed and store in a well ventilated and cool-dark place. Do not use fire in storage place.
	Keep away from oxidizing agents. : See '10. Stability and Reactivity'.
Packaging material	: Use the container regulated in the UN transport regulation.

8. Exposure Controls and Personal Protective Equipment

Controlled exposure level Engineering controls	 Not established. Provide eyes wash facilities and safety shower in the handling and storage place.
	Provide local exhaust device, prevent discharge this product from the facilities or general ventilation to keep concentration levels in the air below the recommended control concentration/permissible concentration. When the mist is generated in the high heat process, provide local exhaust device to keep concentration levels in the air below the recommended control concentration.
	When the gas is generated in the high heat process, provide local exhaust device to keep concentration levels in the air below the recommended control concentration/permissible concentration.
Personal protective equipment	
Respiratory protection	: Wear gas mask as necessary.
Hand protection	: Wear protective gloves.
Eye protection	: Wear safety glasses, goggle type safety glasses, face protection and the like.
Skin and body protection	: Wear impermeable protective clothing, protective apron and the like.
Hygiene measures	: Do not eat, drink or smoke when handling. Wash hands thoroughly after handling. Protective equipment shall be inspected regularly according to the
	protective equipment checklist.

9. Physical and Chemical properties

· · ·	
Physical state	:Liquid
Colour,	:Colourless
Odour	:Odourless (normal temperature)
Melting point	:No information
Boiling point, initial boiling point and boiling range	:140°C
Flammability(solid, gas)	: Non flammable
Lower and upper explosion limit / flammability limit	:No information
Flash point	:No information
Auto-ignition temperature	:No information
Decomposition temperature	:No information
рН	:13.5≦
Kinematic viscosity	:No information
Solubility	:Miscible in water.
	:Soluble in alcohol.
Partition coefficient ;n-octanol/water(log value)	:No information
Vapour pressure	: 0.41 kPa (20°C)
Density and/or relative density	:1.4791 (20/4°C)
Relative vapour density	:No information
Particle characteristics	:No information

10. Stability and Reactivity

Reactivity	: Hydroxides precipitate from aqueous solutions of many metal salts. Fats are saponified to produce the fatty acids sodium and glycerin.
Chemical stabillity	: Stable under normal conditions. It absorbs carbon dioxide in the air to produce potassium carbonate.
Possibility of hazardous reactions	: Generate heat vigorously when contact with acids. The chemical corrodes aluminium, tin, zinc, chromium, and their alloys, releasing combustible hydrogen gas.
Conditions to avoid	: Light, heat.
Incompatible materials	: Acids, metals.
Hazardous decomposition products	: Potassium oxide, hydrogen.

11. Toxicological Information

Acute toxicity (Oral)	: Harmful if swallowed
Acute toxicity (Dermal)	: Classification not possible
Acute toxicity (Inhalation: Gases)	: No classification
Acute toxicity (Inhalation: Vapours)	: Classification not possible
Acute toxicity (Inhalation: Dusts and mists)	: Classification not possible
Skin corrosion/irritation	:Causes severe skin burns
	Potassium hydroxide: The substance (solid) is described to be corrosive.
	Exposure to human skin caused chemical burns (3rddegree). Battery
	electrolyte (25% solution of the substance) caused tissue corrosion
	associated with small perforation. In rabbit skin irritation tests,
	corrosiveness was observed. Thus, it was classified into category 1B.
Serious eye damage/eye irritation	:Causes serious eye damage
	Potassium hydroxide : Based on the statements that it caused irreversible
	damage to humans and that it was corrosive to rabbits, it was classified into
	category 1
Respiratory sensitization	:Classification not possible
	· - · · · · · · · · · · · · · · · · · ·

	Date of revision: 2023/9/28
Skin sensitization	:Classification not possible Potassium hydroxide: Skin sensitization studies in guinea pigs gave
	negative results. Potassium ion (K+) and hydroxide ion (OH-) exist in living
	organisms. Thus, it is unlikely that the substance causes skin sensitization.
	However, the classification was not possible because the details of the test
	are unknown and there is no human data.
Germ cell mutagenicity	: No classification
Gerni cell mutagenicity	Potassium hydroxide: There are no in vivo data on this substance.
	As for in vitro, a bacterial reverse mutation test and a mammalian cell
	chromosome aberration test were negative. In SIDS, the mutagenicity of
	this substance was evaluated from comprehensive information on this
	substance, sodium hydroxide, potassium chloride, and potassium carbonate. Based on this evaluation, It is stated in SIDS that these
	substances are not considered to be genotoxic.
Carolinaganiaity	: Classification not possible.
Carcinogenicity Reproductive toxicity	: Classification not possible.
Specific target organ toxicity	:Causes damage to organs (respiratory organs)
(single exposure)	Potassium hydroxide: The substance acts as strong alkali on skin and
(angle exposure)	mucosa, and inhalation exposure to dust or mist may cause upper
	respiratory tract irritation and tissue damages, leading to nasal septum
	damage and pulmonary edema. Thus, it was classified into category 1
	(respiratory organs).
Specific target organ toxicity	: Causes damage to organs (respiratory organs) through prolonged or
(repeated exposure)	repeated exposure
	Potassium hydroxide: Human studies have shown that inhalation of the
	substance (dust, mist) causes upper airway inflammation, which may result
	in nasal septum ulceration as a chronic effect. However, there is no studies
	on airborne concentrations and incidence of lesions. Exposure to dust or
	mist of the substance may cause nasal septum lesions and irritation of the
	eyes and respiratory tract. Although there is not sufficient data, it is clear
	that the substance is alkaline and inhalation causes respiratory
	inflammation. Thus, the substance was classified into category 1
	(respiratory organs)
Aspiration hazard	:May be fatal if swallowed and enters airways
	Potassium hydroxide: Studies show that in fatal cases of unintentional
	ingestion of the substance, the cause of death involves aspiration into the
	esophagus to trachea and pneumonia, and aspiration of alkali into airway
	causes fatal injuries to the larynx, trachea/bronchus, and lung. Thus, it was
	classified into category 1
Others	: No information.

12. Ecological Information

Ecotoxicity		
Hazardous to the aquatic environment (acute)	: Classification not possible.	
Hazardous to the aquatic environment (chronic)	: Classification not possible.	
Persistence/degradability	: No information	
Bioaccumulation	: No information	
Mobility in soil	: No information	
Hazardous to the ozone layer	Classification not possible.	
Other hazard	: No information.	

13. Precautions for Disposal

Residual wastes	: Before disposal, to be the low level hazard state, perform the process of detoxification, stabilization and neutralization and the like as much as possible.
	In the disposal, follow the relevant laws and regulations and the standards of the local government.
	Entrust disposal to industrial waste disposal contractor who has received the permission of prefectural governor, or if the local government is performing waste disposal, entrust them disposal.
Contaminated container and packages	: Recycle containers after cleaning up or dispose of properly in accordance with relevant laws and local regulations. If dispose the empty container, dispose after removing contents completely.

14. Transport Information

International regulations Inland transport Sea transport Air transport	: Follow the regulation under ADR/RID. : Follow the regulation under IMO. : Follow the regulation under ICAO/IATA.
UN number UN class Proper shipping name Packing group Marine pollutant Emergency response guideline number (North America)	: 2797 (Electrolyte (Alkaline)) : Corrosive substance /Class 8 : BATTERY FLUID, ALKALI : II : Not applicable : 154

15. Regulatory Information

TSCA (Toxic Substances Control Act)

Each component parts of battery is listed in the TSCA Registry as follows.

Components	Chemical Formula	TSCA Status
Potassium Hydroxide	КОН	Listed

16. Other Information

Reference:

Globally Harmonized System of classification and labeling of chemicals, (6th ed., 2015), UN JIS Z 7253:2019

1) NITE GHS classification data.

2) SIDS

3) NITE CHRIP (<u>http://www.safe.nite.go.jp/japan/sougou/view/SystemTop_jp.faces</u>)

Notice:

The contents described in this SDS are prepared based on the data and information currently available to us. However, it does not intend to be any guarantees in regard to content, physical and chemical properties, hazards, etc.

Please handle this product in the responsibility of the user after referring to this SDS.

In addition, the precautions are intended for normal handling. Please use under implementing safety measures that are suitable for application/usage if you want to special handling.